



for Passive Groundwater Sampling

Graphic Ordering Sheet	
Choose items for <i>each</i> well	
Copy and itemize for additional wells	
	WELL CAPS
WELL ID:	2inch/50mm Well Cap
1) WELL CAP Selection: <u>SNAP-WellCap2</u>	4inch/100mm Well Cap
>2-inch/50mm (x, blank) <u>SNAP-WellCap4</u> >4-inch/100mm (x, blank)	TRIGGER SYSTEM
Custom Adapter(y/n)(specify)	Manual Trigger
2) TRIGGER Selection:	Pneumatic Trigger
SNAP-MTC: >Manual Trigger Construct(x, blank) SNAP-MTL: >Manual Trigger Line(ft/m) OR SNAP-PTC: >Pneumatic Trigger Construct(x, blank) SNAP-PA, required with SNAP-PTC(x, if PTC is marked) SNAP-PTL: >Pneumatic Trigger Line(ft/m) 3) SNAP SAMPLER MODULE Selection: SNAP-40(#) SNAP-125-350(#) Maximum: 6 Snap Sampler modules total A) POTTILE Galactic SNAP-125-350(#)	
4) BOTTLE Selection: One bottle required for each Snap Sampler, for each sample collected First event normally requires two sets of bottles (one to deploy, one to redeploy after first sample is collected) SNAP-VOAPack SNAP-125P (#) SNAP-350P (#)	
5) WEIGHT: For submergence greater than 100ft/30m SNAP-Weight3, 3lb/1.4kg weight(x, blank) SNAP-Weight6, 6lb/2.8kg weight(x, blank)	